

# ZKD1502

## Touch Monitor

15" TFT LCD Panel

5 wires touch screen

12V 3A Power adapter



## Features

- Taiwan EETI touch card;
- Factory-control Grade A LED panel;
- 24-hour non-stop operation;
- Efficient heat dissipation system;
- Foldable Touch Monitor;
- Support Windows platforms;
- High gloss black edges;
- Support USB touch interface;
- Support VGA input format;
- Multiple installation methods available;
- Integrated touch function and LCD solution.

## Specifications

Model	ZKD1502	ZKD1503
Type	15" TFT LCD Panel	15" AUO TFT LCD Panel
Dimension	350*44*275mm (L*W*H)	
Max Resolution	1024×768 @ 60Hz	
Brightness	250cd/m2	
LED Backlight Lifespan	50,000 hours	
Input Voltage	100-240 VAC, 50-60 Hz	
Output Voltage	12 volts at 4 amps max	
Power Consumption	12W(Max)	
Touch Panel Type	Resistive touch (Standard) Capacitive touch (Optional)	Resistive touch from Taiwan Higgstec (Standard) Capacitive touch from Taiwan Higgstec (Optional)

# ZKP8001

## Thermal Receipt Printer

Fast, Reliable



### Features

- Low noise and high-speed printing;
- Support cash drawer driver;
- Low power consumption;
- Low operating costs (No Ribbons or Ink cartridges);
- Built-in data buffers;
- Support different density bitmap graphics printing;
- High-speed printing using embedded;
- soft font for all interfaces;
- Support NV image downloading and printing;
- Support one-dimensional code, two-dimensional code printing.

### Specifications

Print Method	Direct Thermal Line Printing
Print Speed	300mm/sec
Print Command	Compatible with ESC/POS
TPH	100 km
Interface(Optional)	Serial/USB/Ethernet/Bluetooth/Wi-Fi
Paper Cutter	Auto Cutter: Full or Partial Cut
Weight	2kg
Dimension	190*145*145mm(L*W*H)
Output (Power Supply)	DC 24V/2.5A
Cash drawer (Power Supply)	DC 24V/1A

# ZKB201

## Barcode Scanner

2-dimensional barcode scanner

Integrates the lens and decoding function



## Features

- Identifying all 1-dimensional bar codes and most 2-dimensional bar codes;
- High Identification ability of barcodes;
- Equipped with four 625±10nm red lights;
- Cursor indicator and the blinking function;
- White and black available, fireproof, waterproof, shock-proof;
- Uses the standard 10-core RJ45 interface;
- Identifying bar codes with low contrast;
- Ultra-long reading Depth of Field (DoF);
- Supports secondary development for various project types.

## Specifications

Decode Error Rate	1/8 million
Anti-knock	1.8m free fall to test
Power (Light Source)	< 70mW
Precision	>=4mil
Scan Angle	Rotation: 360°, Tilting: ±50°, Deflection: ±50°
Dimension	163*70*102mm(L*W*H)
Operating Current	130mA
Standby Current	20mA
Maximum Peak	220mA
Voltage	DC3.5V-5.5V(Standard)

# ZKC01

## Metal Cash Drawer



### Specifications

Type	4 Bills, 8 Coins
Check Slots	1 Check Slots
Lock	3 Position Lock
Dimensions	410 mm (W) x 420 mm (L) x 100 mm (H) (excluding rubber feet)
Material	The shell is made of cold-pressed steel plate and the drawer is made of ABS plastic.
Pulse Amplitude	12VDS - 24VDS
Money Clip	Standard Wire Clip
Gross Weight	6.5kg
Net Weight	6.2kg
DC	12V, 24V
Interface	RJ11(Directly connected with receipt printer and cashier interface 12V or 24V )
Color	Black

